

NETTUN@ 7000^{open}

All-in-one POS system with integrated printer

The “Nettun@7000open” is a perfect combination between a traditional cash register and a “PC-based” Point of Sale.

With its 10.1 tiltable touch screen, the integrated thermal printer for receipts equipped with automatic cutter and the adjustable customer display, “Nettun@7000open” is an integrated system for management of Point of Sales in any kind of retail and restaurant business.

The product is characterized by an Intel-based architecture that allows to match operators needs and to manage retail, hospitality, industrial control and other applications.



COMPATIBLE WITH APPLICATIONS DEVELOPED FOR MICROSOFT

WIDE I/O CONNECTIONS FOR VARIOUS PERIPHERALS

FACTORY CUSTOMIZATION OF SPECIFIC MODELS WITH IDENTITY VALIDATION
OPTIONS ON REQUEST

POSSIBILITY TO CONNECT DRAWER, EXTERNAL MONITOR, ADDITIONAL KEYBOARD,
BARCODE READER, SLIP PRINTER



TOUCH SCREEN with tiltable operator panel



EASY paper-roll insertion



FULL CHOICE of interfaces and USB ports

TECHNICAL SPECIFICATIONS

MAIN CHARACTERISTICS

Touch Screen	10.1" TFT 16:9 colour monitor Backlit (1024x600) 4-wire resistive touch technology Adjustable tilt
Customer display	LCD Alphanumeric 20x2 Pop-up / adjustable
Mass storage	SSD card ≥ SATA 32 GB capacity

PRINTER

Technology	Thermal
Speed (line/sec.)	200 mm/sec. - 80 mm
Cutter	Manual & Automatic
Paper loading	Easy loading
Paper roll width (mm)	80 mm
Paper roll diameter (max.)	Up to 80 mm
Fonts characters	2, normal and double height 36/44/52 (25/30/36 with roll width 58/60 mm)

OTHER CHARACTERISTICS

Sensors	End slip paper Near end slip paper
Connectable devices	Drawer, external monitor, additional keyboard, barcode readers, slip printer, pen drives
Interfaces	2 RS-232 (RJ45 connector) 4 host USB 2.0 1 RJ45 Ethernet 1 RJ45 Drawer connection 1 RJ12 Remote display 1 Customer Display interface 1 VGA Display port 1 HDMI Display port 1 line-out jack 1 microphone jack
Electrical Characteristics	External power supply 24V 60W 100 Vac/60 Hz - 240 Vac/50Hz electric cable Length terminal-Power supply: 1,5m Length Power supply-plug: 1,5 m
Power On/Off button	On the rear side of the machine, inside the connection area
Dimensions (wxdxh)	360x360x180 mm (260 mm with customer display pulled out)

Performance relates to use of the product under optimal conditions.
Right reserved to modify technical specifications.
Registered trademarks are the property of their respective owners.
Nettun@ 7000open is distributed by Olivetti S.p.A.
(09/2017) - Code: 49586-00-w